

RAMBOLT

Order Code	Size	Max Fix Thickness	Hole Size	Box Qty	A torque controlled shield anchor suitable for use in concrete and solid brickwork. Zinc Plated and Yellow Passivated. Guide to Fixing Selection S - indicates Shield only L - indicates Loose Bolt P - indicates Projection Bolt EF - indicates Forged Eyebolt HF - indicates Forged Hookbolt EG 610L Indicates 6 = 6mm Bolt Thread 10 = 10mm Max Fixture Thickness				
75-509	M6EF		10	25					
75-510	M8EF		14	25					
75-511	M10EF		16	10					
75-512	M12EF		20	10					
75-513	M6HF		10	25	Order Code	Size	Max Fix Thickness	Hole Size	Box Qty
75-514	M8HF		14	25	75-534	610P	13	10	50
75-515	M10HF		16	10	75-535	625P	28	10	50
75-516	M12HF		20	10	75-536	650P	53	10	50
75-517	610L	10	10	50	75-537	815P	17	14	50
75-518	625L	25	10	50	75-538	840P	42	14	50
75-519	640L	40	10	50	75-539	880P	82	14	25
75-520	810L	10	14	50	75-541	1030P	30	16	50
75-521	825L	25	14	50	75-542	1050P	50	16	25
75-522	840L	40	14	50	75-543	1070P	70	16	25
75-523	1010L	10	16	50	75-544	1090P	90	16	25
75-524	1025L	25	16	50	75-546	1225P	28	20	25
75-525	1050L	50	16	50	75-548	1270P	68	20	10
75-526	1075L	75	16	25	75-549	1625P	25	25	10
75-527	1210L	10	20	25					
75-528	1225L	25	20	25	75-500	M 6S		10	50
75-529	1240L	40	20	25	75-501	M 8S		14	50
75-530	1260L	60	20	25	75-502	M10S		16	50
75-531	1615L	15	25	10	75-503	M12S		20	25
75-532	1630L	30	25	10	75-504	M16S		25	10
75-533	1660L	60	25	10					

Dynabolt Plus

Order Code	Diam. X Length (mm)	Box Qty	Order Code	Diam. X Length (mm)	Box Qty
75-300	6 x 25	100	75-311	12 x 55	25
75-301	6 x 38	100	75-312	12 x 70	25
75-302	6 x 57	100	75-313	12 x 98	20
75-303	8 x 40	100	75-314	12 x 126	20
75-304	8 x 66	50	75-315	16 x 62	20
75-305	8 x 92	50	75-316	16 x 106	10
75-306	10 x 41	50	75-317	16 x 140	10
75-307	10 x 49	50	75-318	20 x 81	10
75-308	10 x 76	50	75-319	20 x 113	5
75-309	10 x 103	25	75-320	20 x 157	5
75-310	10 x 125	25			

HEX NUTS & BOLTS Zinc Cobalt Plating & Stainless Steel A4

A full range of Hex Nuts and Bolts either Countersunk or Round Head is available in both Zinc Cobalt plating and Stainless Steel A4-316. Call our Sales Hotline on 01560 32 38 32 for further details and a competitive quotation.

THE PRODUCTS LISTED ON THESE PAGES ARE A SELECTION FROM ONE OF THE WORLD'S LARGEST MANUFACTURERS OF CONSUMABLES AND TOOLS FOR THE CONSTRUCTION INDUSTRY. FAMOUS BRAND NAMES AND MARKET LEADERS IN THEIR FIELD, THEIR PRODUCTS OFFER EXCELLENT PERFORMANCE AND ASSURED QUALITY AT A COST NOT MUCH DIFFERENT FROM THOSE 'UNBRANDED' PRODUCTS IN THE MARKET PLACE.

Timber Fix Screws

Order Code	Size mm	Head/Drive	Steel Thickness	Timber Thickness
75-150	4.8 x 36	Wafer pz	1.5 - 3.0	6 - 20
75-151	4.2 x 38	Csk Rib pz	1.5 - 3.0	6 - 22
75-152	4.8 x 45	Csk rib pz	1.5 - 3.0	10 - 27
75-153	5.5 x 50	Csk rib pz	1.5 - 3.0	13 - 30
75-154	5.5 x 61	Csk rib pz	1.5 - 3.0	13 - 40
75-155	5.5 x 80	Wafer pz	1.5 - 3.0	25 - 60
75-156	5.5 x 100	Wafer pz	1.5 - 3.0	45 - 80
75-157	5.5 x 120	Wafer pz	1.5 - 3.0	40 - 100
75-158	5.5 x 57	Csk pz	4.0 - 6.0	18 - 35
75-159	5.5 x 70	Csk pz	4.0 - 6.0	18 - 40
75-160	6.3 x 75	Csk pz	4.0 - 6.0	18 - 50
75-161	5.5 x 42	Csk pz	4.0 - 10.0	10 - 13
75-162	5.5 x 65	Csk pz	4.0 - 10.0	10 - 28
75-163	5.5 x 80	Csk pz	4.0 - 10.0	10 - 42
75-164	5.5 x 90	Csk pz	4.0 - 10.0	35 - 55
75-165	5.5 x 100	Csk pz	4.0 - 10.0	45 - 65

Teks Screws

Order Code	Description	Steel Thickness	Box Qty
75-170	TC13 4.8 x 13	1.5-2.0	500
75-171	TC16 4.8 x 16	1.2-3.5	500
75-172	TC25 5.5 x 25	1.2-3.5	500
75-173	TC50 5.5 x 50	1.2-3.5	3000
75-174	TC62 5.5 x 62	1.2-3.5	1000
75-175	TC75 5.5 x 75	1.2-3.5	1000
75-176	TC100 5.5 x 100	1.2-3.5	500
75-177	TL32 5.5 x 32	4.0-12.5	250
75-178	TL38 5.5 x 38	4.0-12.5	2500
75-179	TL50 5.5 x 50	4.0-12.5	2000
75-180	TL75 5.5 x 75	4.0-12.5	1000
75-181	TL100 5.5 x 100	4.0-12.5	500

Tapcon Masonry Anchors

Order Code	Size mm	Beams Head	Fixing Thickness mm
75-100	4.8 x 32	Csk pozi	0 - 7
75-101	4.8 x 45	Csk pozi	5 - 20
75-102	4.8 x 57	Csk pozi	17 - 32
75-103	4.8 x 70	Csk pozi	30 - 45
75-104	4.8 x 82	Csk pozi	42 - 57
75-105	4.8 x 100	Csk pozi	60 - 75
75-106	6.3 x 32	Csk pozi	0 - 7
75-107	6.3 x 45	Csk pozi	5 - 20
75-108	6.3 x 57	Csk pozi	17 - 32
75-109	6.3 x 70	Csk pozi	30 - 45
75-110	6.3 x 82	Csk pozi	42 - 57
75-111	6.3 x 100	Csk pozi	60 - 75
75-112	6.3 x 125	Csk pozi	85 - 100
75-113	4.8 x 32	Hex 1/4	0 - 7
75-114	4.8 x 45	Hex 1/4	5 - 20
75-115	4.8 x 57	Hex 1/4	17 - 32
75-116	6.3 x 32	Hex 5/16	0 - 7
75-117	6.3 x 45	Hex 5/16	5 - 20
75-118	6.3 x 57	Hex 5/16	17 - 32
75-119	6.3 x 70	Hex 5/16	30 - 45
75-120	6.3 x 82	Hex 5/16	42 - 57
75-121	6.3 x 100	Hex 5/16	60 - 75

Tapcon Drill Bit

Order Code	Description
75-140	4.35 x 110 Percussion Bit
75-141	4.35 x 140 Percussion Bit
75-142	5.15 x 110 Percussion Bit
75-143	5.15 x 140 Percussion Bit
75-144	5.15 x 165 Percussion Bit
75-145	4.35 x 180 SDS+ Bit
75-146	5.15 x 180 SDS+ Bit
75-147	5.15 x 205 SDS+ Bit

Tapcon Accessories (for semi-automatic installation of Tapcon Anchors up to 100 mm long)

Order Code	Description
75-130	CD1000 Condrive Tool boxed set
75-131	CD101 Drill bit holder
75-132	CD102 Drive Sleeve
75-133	CD106 1/4 inch Hex socket to fit 3H range
75-134	CD107 5/16 inch Hex socket to fit 4H range
75-135	CD110 Phillips Drive Adaptor